
This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

| | REVISIONS | | | | | | | | |
|-----|-----------|---|------------|----------|----|--|--|--|--|
| REV | ECR | DATE | INITIAL | APPROVED | | | | | |
| Α | | DELETED -1 ENGRAVE "DTE 1" AND "KPE 1". DELETED -3 "DET 2 (KPE 1)" FROM ENGRAVE NOTE. | 12/21/2012 | RJC | SE | | | | |
| 2 | 16-0071 | -1 CH'D MATERIAL WAS 1018 IS A36/1018/1020 HR, CH'D ENGRAVE NOTE WAS ENGRAVE T/N "RBW6500X01611W142B-3T" IS ENGRAVE T/N, S/N, "MADE IN USA", CH'D DIM WAS 2.955 IS 2.955 ±.033 CH'D MATERIAL WAS 1018 IS A36/10181/1020 HR, CH'D ENGRAVE NOTE WAS ENGRAVE T/N "RBW6500X01611W142B-3T" IS ENGRAVE P/N "RBW6500X01611W142B-3T-3". | 7/12/2016 | RJC | SM | | | | |



NOTE:

- 1. PART OF KIT RBW6505G00431-3T.
- 2. REF. AGUSTA P/N 3T6500X01611W142B.



SHAFT SUPPORT BEARING REMOVAL


RBW6500X01611W142B-3T UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
.XXX ± .005 FRACTIONS ± 1/8
.XX ± .01 ANGLES ± .5° MAT'L


| | FINISH | | .XX ± .01 ANGLES ±.5" | | | | |
|----|------------|-----------|--|--|--|--|--|
| | SPEC | | 1. BREAK ALL SHARP EDGES | | | | |
| | DRAWN BY: | CLOUGH | .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY | | | | |
| | CHECKED: | DUERFELDT | AFTER PLATING 3. INTERPRET DIM AND TOL PER | | | | |
| 3. | OPPS APPR: | ANDERSON | ASME Y14.5M-2009 | | | | |
| | QA APPR: | LINDSAY | USED ON MODEL | | | | |
| 2 | APPROVED: | MACKOVJAK | AW139 | | | | |


| | | | | | | | | | CHECKED: | DUERFE | LDT | AFTER PL | |
|-------------|------|-----|--------|------|-------------|------------------|-----------------------------------|----------|------------|--------|---------|-------------------------|-------------------------------|
| ASSY QTY | YZZA | B/O | Part # | UNIT | Description | Material | B/O INFORMATION OR SPECIFICATIONS | PG. | OPPS APPR: | ANDERS | SON | 3. INTERPRE ASME Y14 | T DIM AND TOL PER .5M-2009 |
| QIII QIII | | | Q17 | | | | | QA APPR: | LINDSAY | | | USED ON MODEL | |
| | | | -1 | 2 | PLATE | A36/1018/1020 HR | | 2 | APPROVED: | MACKO\ | /JAK | | AW139 |
| | | | -3 | 1 | KNOB | A36/1018/1020 HR | | 3 | SCALE | 1:2 | DATE 10 | 0/14/2012 | SHEET 1 OF 3 |
| | | | | | | | | | | | | | |


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

| | revisions | | | | | | | |
|-----|-----------|--|------------|----------|----|--|--|--|
| REV | ECR | DATE | INITIAL | APPROVED | | | | |
| Α | | DELETED -1 ENGRAVE "DTE 1" AND "KPE 1". | 12/21/2012 | RJC | SE | | | |
| 2 | 16-0071 | -1 CH'D MATERIAL WAS 1018 IS A36/1018/1020 HR, CH'D ENGRAVE NOTE WAS ENGRAVE T/N "RBW6500X01611W142B-3T" IS ENGRAVE T/N, S/N, "MADE IN USA", CH'D DIM WAS 2.955 IS 2.955 ±.03. | 7/12/2016 | RJC | SM | | | |









DART

SHAFT SUPPORT BEARING REMOVAL

WG NO. RBW 6500 X 0 1 6 1 1 W 1 4 2 B - 3 T - 1

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
.XXX ± .005 FRACTIONS ± 1/8
.XX ± .01 ANGLES ± .5°
.X ± .1 SURFACES = 125/

MAT'L A36/1018/1020 HR

HEAT
TREAT
TREAT
TREAT
FINISH BLACK OXIDE
SPEC QMSI-6.2.2 REV D
DRAWN BY: CLOUGH
CHECKED: DUERFELDT
OPPS APPR: ANDERSON
AS
QA APPR: LINDSAY

1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009

 QA APPR:
 LINDSAY
 ASME 114.5m-2009

 APPROVED:
 MACKOVJAK
 AW139


 SCALE
 1:2
 DATE
 10/14/2012
 SHEET 2 OF 3

(-1)


PLATE


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

| | REVISIONS | | | | | | | | |
|-----|-----------|--|------------|---------|----------|--|--|--|--|
| REV | ECR | DESCRIPTION | DATE | INITIAL | APPROVED | | | | |
| Α | | DELETED -3 "DET 2 (KPE I)" FROM ENGRAVE NOTE. | 12/21/2012 | RJC | SE | | | | |
| 2 | 16-0071 | -3 CH'D MATERIAL WAS 1018 IS A36/1018/1020 HR, CH'D ENGRAVE NOTE WAS ENGRAVE T/N "RBW6500X01611W142B-3T" IS ENGRAVE P/N "RBW6500X01611W142B-3T-3". | 7/12/2016 | RJC | SM | | | | |









SHAFT SUPPORT BEARING REMOVAL

| DWG NO. R | BW650 |)OXC | 511W14 | 42B-3T-3 | 2 | | | | |
|---------------|-------------|------|--------|---|------------------------------|-----|--|--|--|
| MAT'L A36/10 | 18/1020 HR | | | UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 | | | | | |
| HEAT TREAT | | | | | | | | | |
| FINISH BLACK | OXIDE | | | .XX ± .01 | ANGLES ±.5° SURFACES = 1 | 25/ | | | |
| SPEC QMSI- | 6.2.2 REV D | | | 1. BREAK ALL SHARP EDGES | | | | | |
| DRAWN BY: | CLOUGH | | | .015 x 45° 0 | OR .015R NAL LIMITS APPLY | | | | |
| CHECKED: | DUERFELDT | | | AFTER PLATING | | | | | |
| OPPS APPR: | ANDERSON | | | 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 | | | | | |
| QA APPR: | LINDSAY | | | | USED ON MODEL | | | | |
| APPROVED: | MACKOVJAK | | | AW139 | | | | | |
| SCALE | 1:2 | DATE | 10/ | 14/2012 | SHEET 3 OF | 3 | | | |



KNOB